

Product Overview

STYCCOBOND F66 is a solvent free contact adhesive, which is designed to give a high bond strength for securing PVC and rubber edgings, covings and nosings, floor and wallcoverings

Features

- + Strong initial tack
- + Long open time
- + Solvent free
- + Good drying time
- + Suitable for use over underfloor heating installations
- + STYCCOBOND F66 can be used on substrates of Plaster, Cement Render, Wood, Stone, Metal and UPVC

Benefits

- + No need to hold down for initial tack
- + More time to get the area covered
- + User friendly for installation
- + Quicker flooring install
- + Versatile applications

Product Codes

Styccobond F66 Flooring Adhesive 5l

30128

Guarantee & Approvals

BREEAM; BS EN 13999-1:2013. In-house testing to the test method described in BS EN 13999 parts 2-4. Product does not contain carcinogenic or sensitising volatile substances.



Sizes & options

- + 5 litre container

Product Specification

- + **Open Time:** 60 minutes depending on room temperature
- + **Shelf Life:** 12 months
- + **Colour:** White
- + **Consistency:** Creamy
- + **Coverage:** 5m² per litre using a 1.4mm x 2.5mm trowel

Compatible with Safety & Vinyl Flooring

Product	Code
AKW Safety flooring (0.5m x 2m) : Anthracite 1sqm (2m wide x 0.5m length)	21891-ANT
AKW Safety flooring (0.5m x 2m): Cerulean 1sqm (2m wide x 0.5m length)	21891-CRL
AKW Safety flooring (0.5m x 2m): Dove 1sqm (2m wide x 0.5m length)	21891-DVE
AKW Safety flooring (0.5m x 2m): Rouge 1sqm (2m wide x 0.5m length)	21891-RGE
AKW Safety flooring (0.5m x 2m): Slate 1sqm (2m wide x 0.5m length)	21891-SLT
AKW Safety flooring (0.5m x 2m) : Cement 1sqm (2m wide x 0.5m length)	21891-CMT
AKW Safety flooring (0.5m x 2m): Topaz 1sqm (2m wide x 0.5m length)	21891-TPZ
Vinyl Flooring PVC Coving – Pack of Ten	30085